


**Reduction gear**  
1 450 rpm



### MAIN FEATURES

- ▶ Pump + reducer : longer life time
- ▶ Anti water hammer regulator



### ● SPECIFICATIONS

- Crankshaft pump (radial) 3 ceramic pistons
- Regulator : separated from the manifold with pressure drop to zero
- Integrated detergent application system
- Reducer : reduces the rotation speed of the pump
- Diesel engine
- Pull start
- Welded steel frame and hood, epoxy paint



### OPTIONS

- ▶ 1 - Steel hose reel
- ▶ 2 - Turbo lance
- ▶ 3 - Hose extension
- ▶ 4 - Sanding kit
- ▶ 5 - Wheelbarrow arms
- ▶ 6 - Hydro-ejector kit
- ▶ 7 - Drain cleaning kits

### ● STANDARD EQUIPMENT

- HP hose : 10 m 3/8 double metal braided hose
- HP spray gun : with swivel link (on hose side)
- Lance : 900 mm double lance adjustable high & low pressure
- Quick coupling : on the outlet of the pump
- Pneumatic wheels : Ø 500 mm

Use :



Semi-pro Professional Intensive Super Intensive

### ● MODEL

REFERENCE	FLOW RATE		PRESSURE	POWER			PUMP		WEIGHT
	l/min	l/h		bar	Engine	HP	rpm	Brand	
TID 15 200 Y	15	900	200	YANMAR	10	1 450	INTERPUMP	15W40	100