

THREE PHASE HP WASHERS

Intensive series 12 HP - Ref. IP 21 200



Flector coupling
1 450 rpm



MAIN FEATURES

- ▶ Long life pump
- ▶ Anti water hammer regulator
- ▶ Elastic coupling
- ▶ Pneumatic wheels
- ▶ Lance holders
- ▶ Wheelbarrow arms



SPECIFICATIONS

- Crankshaft pump (radial), 3 ceramic pistons
- Pump safety : VST (thermal safety valve)
- Regulator : separated from the manifold
- Flector coupling : increased elasticity of the motor-pump coupling
- Engine : three phase electric engine
- Magneto-thermal circuit breaker
- Electric cable : 5 m
- Welded steel frame, epoxy paint
- ABS hood

STANDARD EQUIPMENT

- Hose : 10 m 3/8 double metal braided hose
- HP gun : with swivel link (on hose side)
- 1050 mm double lance adjustable high & low pressure
- Quick coupling on the outlet of the pump
- Pneumatic wheels : Ø 400 mm

MODELS

| REFERENCE | FLOW RATE | | PRESSURE | POWER | | PUMP | | | WEIGHT |
|-----------|-----------|------|----------|-------|-----|------|-----------|-------|--------|
| | l/min | l/h | bar | HP | KW | rpm | Brand | Oil | kg |
| IP 21 200 | 21 | 1260 | 200 | 12 | 9,2 | 1450 | INTERPUMP | 15W40 | 115 |

OPTIONS

- ▶ 1 - Steel or ABS hose reel
- ▶ 2 - Time delayed total stop
- ▶ 3 - Turbo lance
- ▶ 4 - Hose extension
- ▶ 5 - Sanding kit



ELECTRIC

