

THREE PHASE HP WASHERS

Intensive series - Galvanized - Ref. : IG 26 150 E




INTERPUMP
GROUP

Flector coupling
1 450 rpm



MAIN FEATURES

- ▶ Long life pump
- ▶ Anti water hammer regulator
- ▶ Elastic coupling
- ▶ Pneumatic wheels
- ▶ Lance holders
- ▶ Wheelbarrow arms




○ SPECIFICATIONS

- Crankshaft pump (radial), 3 ceramic pistons
- Pump safety : VST (thermal safety valve)
- Regulator : separated from the manifold
- Flector coupling : increased elasticity of the motor-pump coupling
- Engine : three phase electric engine
- Magneto-thermal circuit breaker
- Electric cable : 5 m
- Frame and hood : galvanized welded steel

○ STANDARD EQUIPMENT

- Steel hose reel on galvanized tipping frame
- Hose : 20 m 3/8 double metal braided hose
- HP gun : with swivel link (on hose side)
- 900 mm double lance adjustable high & low pressure
- Quick coupling on the outlet of the pump
- Pneumatic wheels : Ø 400 mm



OPTIONS

- ▶ 1 - Time delayed total stop
- ▶ 2 - Turbo lance
- ▶ 3 - Foam gun
- ▶ 4 - Hydro ejector

○ MODEL

REFERENCE	WATER FLOW		PRESSURE	POWER			PUMP	
	l/min	l/h	bar	HP	KW	rpm	Brand	Oil
IG 26 150 E	26	1560	150	12	9,2	1450	INTERPUMP	15W40

Use :

Semi-pro Professional Intensive Super Intensive

