

THREE PHASE HP WASHERS

Stand-alone unit




Flector coupling - 1450 rpm



MAIN FEATURES

- ▶ Long life pump
- ▶ Anti water hammer regulator
- ▶ Elastic coupling
- ▶ Galvanized board



OPTIONS

- ▶ 1 - Time delayed total stop
- ▶ 2 - Turbo lance
- ▶ 3 - Hose extension
- ▶ 4 - Double foam kit

● SPECIFICATIONS

- Crankshaft pump (radial), 3 ceramic pistons
- Pump safety : VST (thermal safety valve)
- Regulator : separated from the manifold
- Flector coupling : increased elasticity of the motor-pump coupling
- Integrated detergent application system
- Three phase electric engine
- Magneto-thermal circuit breaker
- Electric cable : 5 m
- Galvanized welded steel board
- ABS hood

● STANDARD EQUIPMENT

- Hose : 10 m 5/16 single metal braided hose
- HP spray gun : with swivel link (on hose side)
- Single lance with adjustable head & flat jet nozzle



● MODELS

REFERENCE	FLOW RATE		PRESSURE bar	POWER			PUMP		WEIGHT kg
	l/min	l/h		HP	kW	rpm	Brand	Oil	
SM 26 90	26	1560	90	5,5	4	1450	ANNOVI	15W40	70
SM 30 60	30	1800	60	5,5	4	1450	BERTOLINI	80W90	70
SM 38 80	38	2280	80	7,5	5,5	1450	UDOR	15W40	70

