

THREE PHASE HP WASHERS

Intensive series 7.5 HP - Ref. IG 21 150




Flector coupling

1 450 rpm



MAIN FEATURES

- ▶ Long life pump
- ▶ Thermal safety valve
- ▶ Elastic coupling
- ▶ Lance holders
- ▶ Wheelbarrow arms



○ SPECIFICATIONS

- Crankshaft pump (radial), 3 ceramic pistons
- Pump safety : VST (thermal safety valve)
- Regulator : separated from the manifold
- Integrated detergent application system
- Flector coupling : increased elasticity of the motor-pump coupling
- Engine : Three phase electric engine
- Magneto-thermal circuit breaker
- 5 m electric cable
- Galvanized welded steel frame
- ABS hood

○ STANDARD EQUIPMENT

- Hose : 10 m 3/8 double metal braided hose
- HP gun : with swivel link (on hose side)
- 900 mm double lance adjustable high & low pressure
- Quick coupling on the outlet of the pump
- Rubber-tyred wheels : Ø 260 mm

OPTIONS

- ▶ 1 - Steel or ABS hose reel
- ▶ 2 - Galvanized frame
- ▶ 3 - Time delayed total stop
- ▶ 4 - Turbo lance
- ▶ 5 - Hose extension
- ▶ 6 - Sanding kit

Use :



Semi-pro Professional Intensive Super intensive

○ MODELS

REFERENCE	FLOW RATE		PRESSURE bar	POWER		PUMP rpm	PUMP		WEIGHT kg
	l/min	l/h		HP	KW		Brand	Oil	
IG 21 150	21	1260	150	7,5	5,6	1 450	INTERPUMP	15W40	71

