

HOT WATER HP WASHER

Three phase - Standard use - Ref. : DIMACTION 14 160 HW




Direct drive
1450 rpm



MAIN FEATURES

- ▶ Time delayed total stop
- ▶ Easy to handle
- ▶ Lance holder



SPECIFICATIONS

- Crankshaft pump (radial), 3 ceramic pistons
- Total stop : automatic shutdown of engine managed by spray gun
- Regulator : separated from the manifold
- Three phase electric engine
- Detergent application system : integrated
- Electric cord : 5 m
- Boiler : steel construction
- Fuel oil burner
- Thermostat for temperature regulation
- Fuel tank capacity : 16 l
- Wheels : 2 Rubber-tyred wheels 1 castor wheel
- Frame : Steel/polypropylene
- Hood : ABS



OPTIONS

- ▶ 1 - Hose reel
- ▶ 2 - Hose extension
- ▶ 3 - Antiscale kit (curative)



WHAT IS TOTAL STOP?

Time delayed motor start/stop system, thanks to a low voltage power supply system.

Use :



Semi-pro Professional Intensive Super intensive

STANDARD EQUIPMENT

- Blue hose : 10 m 5/16 double metal braided
- HP spray gun : with link
- 700 mm single lance: with adjustable head and flat jet nozzle

MODEL

REFERENCE	FLOW RATE		PRESSURE	POWER		PUMP	TEMPERATURE	WEIGHT		
	l/min	l/h	bar	HP	kW				rpm	Brand
DIMACTION 14 160 HW	14	840	160	5,5	4,1	1450	ANNOVI	15W40	65/140	92

