

THREE PHASE HP WASHERS

Intensive series 12 HP - Ref. : IG 21 200



Flector coupling 1 450 rpm



MAIN FEATURES

- ▶ Long life pump
- ▶ Thermal safety valve
- ▶ Elastic coupling
- ▶ Lance holders
- ▶ Wheelbarrow arms



● SPECIFICATIONS

- Crankshaft pump (radial), 3 ceramic pistons
- Pump safety : VST (thermal safety valve)
- Regulator : separated from the manifold
- Flector coupling : increased elasticity of the motor-pump coupling
- Engine : three phase electric engine
- Magneto-thermal circuit breaker
- Electric cable : 5 m
- Frame and hood : galvanized welded steel

● STANDARD EQUIPMENT

- Hose : 10 m 3/8 double metal braided hose
- HP gun : with swivel link (on hose side)
- 900 mm double lance adjustable high & low pressure
- Quick coupling on the outlet of the pump
- Pneumatic wheels : Ø 400 mm

OPTIONS

- ▶ 1 - Time delayed total stop
- ▶ 2 - Turbo lance
- ▶ 3 - Foam gun
- ▶ 4 - Hydro ejector

Use :



Semi-pro Professional Intensive Super Intensive

● MODEL

REFERENCE	WATER FLOW		PRESSURE	POWER		rpm	PUMP		POIDS
	l/min	l/h	bar	HP	kW		Brand	Oil	kg
IG 21 200	21	1260	200	12	9,2	1450	INTERPUMP	15W40	115

