

Reduction gear 1 450 rpm



MAIN FEATURES

- ▶ Pump + reduction gear : longer lifetime
- ▶ Anti water hammer regulator
- ▶ Easy access to pump and engine components
- ▶ Lifting points



COMBUSTION ENGINE

HP WASHER SPECIFICATIONS

- Crankshaft pump (radial) 3 ceramic pistons
- Regulator separated from the manifold with pressure drop to zero
- Reduction gear : reduces the pump rotation speed
- Petrol engine with lack of oil safety or Diesel depending on model
- Electric start or pull start : depending on model
- Plate : mounted on silent blocs
- Plate and hood : welded steel, epoxy paint
- Water recycled to tank
- Water supply managed by float
- Water level visible

TRAILER SPECIFICATIONS

- GVW* : 1 600 kg
- Unloaded weight : 400 kg
- Trailer : 1 braked axle 1 600 kg
- Supporting frame : galvanized steel
- Anti-roll water tank : 1100 l
- Water filters :
 - 50 µ at the inlet of the pump
 - Filter screen at tank inlet
- 2 wheels : 185R14C outside the frame
- Lifting points : 2 rear + 1 front
- Stabilizer stand : on the rear anti-theft
- Hitch : ALKO ring hitch 68 x 42 mm
- Axle : ALKO
- Parallelogram drawbar ALKO : rheight adjustable - Min. : 20 cm - Max. : 60 cm
- Jockey wheel: automatic
- Coasting brake : automatic pullback, parking break
- Built-in lights
- Lighting : LED 12 V
- Socket : 13 pin socket
- Washbasin : built-in
- CE approved material

OPTIONS

- ▶ 1 - Antifreeze tank : 28 l
- ▶ 2 - Detergent kit
- ▶ 3 - Spare wheel holder
- ▶ 4 - Spare wheel
- ▶ 5 - Coupling head

STANDARD EQUIPEMENT

- HP hose reel : manual, in steel
- HP hose : 20 m 3/8 double braided hose
- HP spray gun : with swivel link (on hose side)
- 900 mm double lance adjustable high & low pressure
- 700 mm turbo lance

EQUIPEMENT REM TIE 41 150 HDEL

- HP hose reel : manual, in steel
- HP hose : 30 m 3/8 double braided hose
- HP spray gun : with swivel link (on hose side)
- 900 mm double lance adjustable high & low pressure
- 700 mm turbo lance
- 2 unblocker nozzles

EQUIPEMENT REM TIE 15 500 HDL

- Special HP hose : 20 m 3/8 double braided hose
- HP spray gun with stainless steel half lance : with swivel link (on hose side)
- 400 mm stainless steel lance : with 25° HP nozzle
- 400 mm stainless steel lance : with turbo nozzle

Use :



MODELS

REFERENCE	FLOW RATE		PRESSURE	POWER				PUMP			
	l/min	l/h		bar	Engine	Fuel	Capacity	HP	Start	rpm	Brand
REM TIE 18 240 HEL	18	1100	240	HONDA	Petrol	6,1 l	13	Pull start	1450	INTERPUMP	15W40
REM TIE 41 150 HDEL	41	2 460	150	HONDA	Petrol	20 l	24 bi-cylinder	Electric	1450	INTERPUMP	15W40
REM TIE 15 500 HDL	15	900	500	HONDA	Petrol	20 l	24 bi-cylinder	Electric	1450	INTERPUMP	15W40
REM TID 15 200 YDEL	15	900	200	YANMAR	Diesel	5,4 l	10	Electric	1450	INTERPUMP	15W40

Please check that you have the appropriate driving license by referring to the legislation in force.

