

THREE PHASE HP WASHERS

Very high pressure - Intensive - Ref. : IG 21 350




Flector coupling 1 450 tr/min



MAIN FEATURES

- ▶ Long life pump
- ▶ Elastic coupling
- ▶ Pneumatic wheels
- ▶ Equipment ensuring great work confort



○ SPECIFICATIONS

- Crankshaft pump (radial), 3 ceramic pistons
- Pump safety : VST (thermal safety valve)
- Regulator : separated from the manifold with pressure drop to zero
- Flector coupling : increased elasticity of the motor-pump coupling
- Engine : three phase electric 20 HP engine
- Magneto-thermal circuit breaker
- Electric cable : 5 m
- Frame and hood : galvanized welded steel

○ STANDARD VHP EQUIPMENT

- Hose : 20 m 3/8 double metal braided
- HP gun : with swivel link (on hose side)
- 900 mm single lance: with adjustable head & flat jet nozzle
- 700 mm turbo lance with rotating nozzle

OPTIONS

- ▶ 1 - Hose extension

Use :



Semi-pro Professional Intensive Super Intensive

○ MODEL

REFERENCE	FLOW RATE		PRESSURE	POWER			PUMP		WEIGHT	DIMENSIONS
	l/min	l/h	bar	HP	kW	rpm	Brand	Oil	kg	cm (Lx l x h)
IG 21 350	21	1 260	350	20	15	1 450	UDOR	15W40	158	131 x 77 x 79

Check our recommended very high pressure personal protective equipment

